

LCDBASE-T
CONNECT A DISPLAY ANYWHERE

LCDBase-T delivers power, video, USB, Audio, Backlight Control, environmental sensing and computing to a display over **standard CAT5/6 Ethernet Cable** and up to 300' distances

reinventing Display Interfacing

Single Wire Display Solutions



DISPLAY LOGIC

LCD Enhancements and Interfacing

DLM3245LBT.0

Display Logic leverages years of experience in unique display interfacing to offer a 32" high brightness low power LCD with single wire Power over Ethernet and Zero Client computing

| | |
|--------------------|-------------------------------------|
| Outside Dimensions | 781.05 (W) x 476.25 (H) x 171.5 (D) |
| Chassis | NEMA4 Rated, Powder Coated Aluminum |
| Display Area (mm) | 697.69 (W) x 392.26(H) mm |
| Brightness | 1,200 cd/m2 |
| Resolution | 1366 x 768 (WXGA) |
| Contrast Ratio | 5000 : 1 |
| Viewing Angle | 176°(H), 176°(V) |
| Display Colors | 16.7M colors |
| Response Time | 7ms (Typical) |
| Power Consumption | 45W |
| Connectivity | Ethernet/RJ45 |
| Mount | VESA 200x200, 200x400 (mm) |

Call or Email to learn about Display Logic's expertise in unique display interfacing and other LCDBase-T Products